

# High Performance Flexible Cable

## Cable Type 106


### Ultimate Performance DC - 26.50 GHz

#### Specifications


Cable Code	Standard	106
	Armored	106x
Frequency Range	DC - 26.50 GHz	
Outer Diameter [mm]	6.20	
Impedance [Ohms] (@ sea level and +25°C)	50 ± 2	
Velocity of Propagation [% , ± 2%]	83.00	
Capacitance [pF/m]	79.00	
Dielectric Strength (60 Hz) [KV rms]	-	
Max. Operating Voltage (60 Hz, @ sea level) [KV rms]	-	
Nominal Insertion Loss vs. Frequency [dB/m]	2.00 GHz	0.30
	4.00 GHz	0.40
	6.00 GHz	0.50
	8.00 GHz	0.60
	10.00 GHz	0.68
	12.00 GHz	0.74
	18.00 GHz	0.92
	25.00 GHz	1.10
	26.50 GHz	1.15
Nominal CW Power vs. Frequency (@ sea level and +20°C) [Watts]	2.00 GHz	800.00
	4.00 GHz	520.00
	6.00 GHz	450.00
	8.00 GHz	380.00
	10.00 GHz	350.00
	12.00 GHz	310.00
	18.00 GHz	270.00
	25.00 GHz	215.00
	26.50 GHz	210.00
RF Leakage @ 9.5 GHz	>100 @ 18.0 GHz dbC	
Operating Temperature Range	-65 to +165	
Center Conductor	Material	Solid Copper, silver-plated
	Diameter [mm]	1.63
Dielectric	Material	Low-density EPTFE
	Diameter [mm]	4.42
	Dielectric Constant	1.5
Outer Conductor Construction	silver-plated copper foil, silver-plated copper braid	
Outer Jacket	FEP	
Weight [grams/m]	90.00	
Connector Retention Force [N]	130.00	
Minimum Bend Radius, Inside, Static [mm]	20.00	
Minimum Bend Radius, Inside, Dynamic [mm]	80.00	

#### Characteristics:

#### Cross Section View:



#### Attenuation & Power Graph:



Spectrum Elektrotechnik GmbH | Olshewskibogen 1 | 80935 Munich, Germany

www.spectrum-et.com | sales@spectrum-et.com | +49 (0)89 / 354 804-0 | +49 (0)89 / 354 804-90

Specifications are subject to change without notice.