

HandyForm-II (solid dielectric) Cable

Cable Type 165 (422-600)

Frequency Range: DC - 40.00 GHz

General		
Cable Model No.	422-600	
Cable Code for Cable Assemblies	165	
Max. Operating Frequency (GHz)	40.00	
Mechanical		
Outer Diameter	inches	0.0870"
	mm	2.20
Outer Conductor Construction	Seamless Aluminum	
Dielectric Material	solid PTFE	
Dielectric Dia. (mm)	1.68	
Dielectric Constant	2.0	
Center Conductor Material	copper clad steel	
Center Conductor Finish	silver-plated	
Center Conductor Dia. (mm)	0.51	
Weight (grams/m)	12.00	
Safe Bending Radius for a 360° bend with proper tooling (mm)	3.20	
Electrical		
Impedance (Ohms @ sea level and +25°C)	50 ± 1	
Velocity of Propagation (% , ±2 %)	69.90	
Capacitance (pF/m)	105.00	
Dielectric Strength (KV _{rms} @ 60 Hz)	5.00	
Max. Operating Voltage (KV _{rms} @ 60 Hz and sea level)	1.50	
Nominal Insertion Loss vs. Frequency [dB/m]	0.50 GHz	0.42
	1.00 GHz	0.64
	5.00 GHz	1.60
	10.00 GHz	2.40
	18.00 GHz	3.40
Nominal CW Power vs. Frequency (@ sea level and +20°C) [Watts]	0.50 GHz	195.00
	1.00 GHz	130.00
	5.00 GHz	47.00
	10.00 GHz	31.00
	18.00 GHz	22.00
Environmental		
Operating Temperature Range (°C)	-54 to +110	

Characteristics:

Additional Information:

- [Connector Code details](#)
- [Information on armor](#)
- [Ordering Information](#)

Spectrum Elektrotechnik GmbH | Olschewskibogen 1 | 80935 Munich, Germany

✉ www.spectrum-et.com | ✉ sales@spectrum-et.com | ☎ +49 (0)89 / 354 804-0 | 📠 +49 (0)89 / 354 804-90

Specifications are subject to change without notice.