

HandyForm-I (solid dielectric) Cable

Cable Type 67 (501-19)

Frequency Range: DC - 18.00 GHz

General		
Cable Model No.	501-19	
Cable Code for Cable Assemblies	67	
Max. Operating Frequency (GHz)	18.00	
Mechanical		
Outer Diameter	inches	0.1410"
	mm	3.60
Outer Conductor Construction	Copper Braid/Tin Composite, 97% shield coverage	
Dielectric Material	solid PTFE	
Dielectric Dia. (mm)	2.98	
Dielectric Constant	2.0	
Center Conductor Material	copper-covered steel	
Center Conductor Finish	silver-plated	
Center Conductor Dia. (mm)	0.91	
Weight (grams/m)	40.00	
Safe Bending Radius for a 360° bend with proper tooling (mm)	6.50	
Electrical		
Impedance (Ohms @ sea level and +25°C)	50 ± 1	
Velocity of Propagation (% , ±2 %)	69.50	
Capacitance (pF/m)	97.00	
Dielectric Strength (KV _{rms} @ 60 Hz)	5.00	
Max. Operating Voltage (KV _{rms} @ 60 Hz and sea level)	1.90	
Nominal Insertion Loss vs. Frequency [dB/m]	0.50 GHz	0.26
	1.00 GHz	0.42
	5.00 GHz	1.22
	10.00 GHz	2.05
	18.00 GHz	3.30
Nominal CW Power vs. Frequency (@ sea level and +20°C) [Watts]	0.50 GHz	450.00
	1.00 GHz	290.00
	5.00 GHz	110.00
	10.00 GHz	72.00
	18.00 GHz	48.00
Environmental		
Operating Temperature Range (°C)	-54 to +110	

Characteristics:

Additional Information:

- [Connector Code details](#)
- [Information on armor](#)
- [Ordering Information](#)

Spectrum Elektrotechnik GmbH | Olschewskibogen 1 | 80935 Munich, Germany

🌐 www.spectrum-et.com | ✉ sales@spectrum-et.com | 📞 +49 (0)89 / 354 804-0 | 📠 +49 (0)89 / 354 804-90

Specifications are subject to change without notice.